


Grid computing for medical image processing

Johan Montagnat

GARR conference “Health Science Community”

Roma, December 12, 2007

- **DataGrid project (2001-2003): WP10 “biomedical applications”**
 - Grid infrastructures discovery
 - From “biology” to “biomedical” (life-science area)
 - First requirements analysis
 - Porting of first pilots and infrastructure testing
- **EGEE-I (2004-2006): NA4/biomed: pilot application area**
 - Entering production mode
 - Middleware steering and infrastructure testing role
 - More applications porting (12 applications in the biomed VO)
- **EGEE-II (2006-2008): NA4/biomed divided in 3 sectors**
 - Medical imaging, bioinformatics, drug discovery



- > 90 Computing Elements (> 8 000 CPUs)
- ~21 TB disk space in Storage Elements
- in ~20 countries

- **Regular infrastructure usage for production**
 - > 100 users
 - > 12 applications
 - ~25 Kjobs per month
 - Generally not so compute intensive: many small jobs
- **Much more than computing power expected**
 - High level data management required (mandatory!)
 - Data protection
 - Sharing data, procedures and resources
 - Easing access to application code for non-specialists
 - ...

- **CDSS**
 - UPV (University Polytechnic of Valencia)
- **Pharmacokinetics**
 - UPV (University Polytechnic of Valencia)
- **GATE**
 - LPC (CNRS – Clermont Ferrand)
- **SiMRI3D**
 - CREATIS (CNRS - Lyon)
- **gPTM3D**
 - LRI-LAL-LIMSI (CNRS - Orsay)
- **Bronze Standard**
 - I3S (CNRS – Sophia), INRIA




- **Scientific objectives**

The study of Contrast Agent Diffusion can characterize tumour tissues without requiring biopsy. The process requires obtaining a sequence of MRI volumetric images. Before analyzing the variation of each voxel, images must be co-registered to minimize deformation due to different breath holds.

- **Method**

The co-registration in the abdomen requires deformable registration methods. The Sequence of Images is co-registered with respect to the first volume. Voxel X,Y in all images must refer to the same body location. Co-registration is compute intensive, especially when dealing with many input images.



- **Scientific objectives**


Radiotherapy planning for improving the treatment of cancer by ionizing radiations of the tumours.

Therapy planning is computed from pre-treatment MR scans by accurately locating tumours in 3D and computing radiation doses applied to the patients.


- **Method**

GEANT4 base software to model physics of nuclear medicine.

Use Monte Carlo simulation to improve accuracy of computations (as compared to the deterministic classical approach)



- **Scientific objectives**
 - Better understand MR physics.
 - Study MR sequences in-silico.
 - Study MR artefacts.
 - Validate MR Image processing algorithms on synthetic
 - yet realistic images.
- **Method**
 - Simulate Bloch's electromagnetism equations.
 - Paralle (MPI)l implementation to speed-up computations.



- **Scientific objectives**

Interactive volume reconstruction on large radiological data.

PTM3D is an interactive tool for performing computer-assisted 3D segmentation and volume reconstruction and measurement (RSNA 2004)

Reconstruction of complex organs (e.g. lung) or entire body from modern CT-scans is involved in augmented reality use case e.g. therapy planning.

- **Method**


Starting from an hand-made rough

Initialization, a snake-based algorithm

segments each slice of a medical volume.

3D reconstruction is achieved in parallel

by triangulating contours from consecutive slices.




- **“Embarassingly” parallel problem**
- **Fast turn over of short jobs**
- **Data confidentiality**
- **Interactivity**
- **Fine grain parallelism (MPI)**
- **Workflow-based**
- **Portal**

- **Medical Data Manager**
 - Grid storage interface to DICOM databases
- **Data protection**
 - Encryption (storage/network protection) + access control (storage/network protection). Two existing systems:
 - Hydra key store integrated in gLiteIO (JRA1)
 - Perroquet (Parrot based, IBCP)
- **Data parallel workflows**
 - Data intensive service composition-based applications
- **Fast turn over**
 - Short deadline jobs



Objectives

- Expose a **standard grid interface (SRM)** for **medical image servers (DICOM)**
- Use native DICOM storage format
- Fulfill medical applications security requirements
- Do not interfere with clinical practice





- **Privacy**

- **Fireman** provides file level **ACLs**
- **gLiteIO** provides **transparent** access control
- **AMGA** provides metadata **secured communication** and **ACLs**
- **SRM-DICOM** provides on-the-fly **data anonymization**
 - It is based on the dCache implementation (SRM v1.1)


- **Data protection**

- **Hydra** provides encryption/ decryption **transparently**






1. Image is acquired



2. Image is stored in DICOM server




3. glite-eds-put

4. image metadata
are registered

gLiteO
server


3a. Image is registered

3b. Image key
is produced and
registered





AMGA Metadata





~100 image pairs


~800 EGEE jobs



- **MOTEUR, I3S laboratory, CNRS**
 - <http://egee1.unice.fr/MOTEUR>
- **Service-based approach**
 - Legacy code service wrapper
- **Scufl language (myGrid / Taverna)**
 - Pure data flow approach
- **Grid submission interfaces**
 - EGEE (LCG2, gLite)
 - Grid5000 (OAR, DIET)
- **Transparent parallelism exploitation**
 - Code and data parallelism




AGIR




- A workflow naturally provides application parallelization
- MOTEUR transparently exploits 3 kinds of parallelism


Workflow parallelism




Data parallelism




Service parallelism



- Jobs grouping strategy in sequential branches in order to reduce grid latency



- On the EGEE infrastructure (biomed VO)



- **Guarantee low-latency execution**
 - Submit-or-reject: Jobs execute or are refused immediately.
 - Complementary to job prioritization.
- **Torque + MAUI batch scheduler**
 - Used on most EGEE sites
 - Specific configuration (virtual processors allocation)
 - No interference with normal batch scheduling (shared proc. time)
 - Enables efficient processing of short tasks on grid
- **Special submission queues**
 - Three biomed sites support SDJ queues
 - Tight limits on CPU and wall-clock time
 - Access to queue also limited




Virtualization technologies for grid applications isolation and deployment
<http://hipcal.lri.fr>

cluster


Long distance network

Individual node





Given a Global infrastructure composed of the aggregation of (computing) resources interconnected by Internet or any network (ie: G5000 VPN)


HIPerSpace



Transform the Global infrastructure into an HIPerSpace:
collection of HIPerNodes and HIPerLinks (virtualized resources)
registered in an HIPerNET registrar (P2P)



**HIPerNET engine: select, allocate, schedule
nodes&channels**



Global infrastructure

- **More data protection**
 - Role-based access control
 - Considering multiple actors involved in clinical procedures (patient, doctor, surgeon, radiologist, nurse, anesthetist...)
- **Data semantics**
 - Metadata associated to data
 - Ontologies
 - Content-based data identification, indexing, mining...
- **User interfaces**
 - Integrated in end-users environments
 - Often specific to application
- **Touch the real end-users (physicians, biologists...)**